


## Performance

- Frequency: 50~110GHz
- Insertion loss: 2.5dB
- Isolation: 35dB
- Input P-0.3: >30dBm
- Input/Output VSWR: 1.5:1
- Switching Time: 10ns
- Control Mode: 0/-15V
- Voltage control reflective switch
- Chip size: 1.2\*1.0\*0.05mm

## Function Diagram



## Electrical Specifications (Ta=+25°C, V1~V2=0V/-15V, F=50~110GHz)

| Symbol | Parameter           | Min. | Typ. | Max. | Unit |
|--------|---------------------|------|------|------|------|
| Li     | Insertion Loss      | -    | 2.5  | -    | dB   |
| ISO    | Isolation           | -    | 35   | -    | dB   |
| VSWR   | Input / Output VSWR | -    | 1.5  | -    | -    |


## Absolute Maximum Ratings (Ta=+25°C)

| Symbol | Parameter                   | Value     | Notes              |
|--------|-----------------------------|-----------|--------------------|
| V1,2   | Control Voltage             | 0.5/-30V  |                    |
| Pcw    | Input Continuous Wave Power | >33dBm    |                    |
| Tch    | Channel Temperature         | 225°C     |                    |
| T      | Sintering Temperature       | 310°C     | 30s, N2 protection |
| Tstg   | Storage Temperature         | -65~150°C |                    |


Exceed any of above listed ratings may cause permanent damage.

## Test Curves (Ta=+25°C, (V1,2=-15V))



VSWR



Insertion Loss @ Different temperature



Isolation @ Different temperature



Note: 1, For same pads, choose any of them.

2, RF input/output dual wire length is less than 300μm.

#### PIN Definition

| PIN     | Description                              |
|---------|------------------------------------------|
| RF1、RF2 | RF ports, 50Ω, no block capacitor        |
| RFc     | RF common ports, 50Ω, no block capacitor |
| V1      | Control Ports                            |
| GND     | Bottom must be grounded                  |

#### Truth Table

| V1 | V2 | RFc→RF1 | RFc→RF2 |
|----|----|---------|---------|
| 1  | 0  | OFF     | ON      |
| 0  | 1  | ON      | OFF     |

Note: 1. Low level "0" is -10V~-20V, High level "1" is 0V~0.5V

2. Performance is same under condition of -10V ~ -20V