

Features

- Low – loss RF filter for mobile telephone Band38 LTE-2600 system
- Low amplitude ripple
- Usable passband 50MHz
- Impedance at input and output 50 Ω
- Unbalance to unbalanced operation
- Package size 1. 1mm*0.9mm
- RoHS compatible

Electrical Specification


ITEM		Min.	Typ.	Max.	Unit
Center Frequency			2595		MHz
Insertion Loss	2570~2620 MHz		1.8	2.4	dB
Passband Ripple	2570~2620 MHz		0.4	1.2	dB
VSWR	2570~2620 MHz		1.4	2.0	
Attenuation	10~1580 MHz	35	39		dB
Attenuation	1580~1606 MHz	35	42		dB
Attenuation	1606~2300 MHz	35	43		dB
Attenuation	2300~2400 MHz	35	41		dB
Attenuation	2400~2510 MHz	34	38		dB
Attenuation	2680~2705MHz	30	50		dB
Attenuation	2705~3000 MHz	40	47		dB
Attenuation	3000~6000 MHz	25	30		dB
Input / Output Impedance (Nominal)		50			Ω

Maximum Ratings

Rating	Symbol	Value	Unit
DC Voltage (between any Terminals)	V _{DC}	5	V
Input power at 2570-2620MHz	P	23 dBm /2000hrs@55°C	
Operating Temperature Range	T _A	-30 ~ +85	°C
Storage Temperature Range	T _{stg}	-40 ~ +85	°C
ESD voltage (Machine Model)	V _{ESD}	50	V
ESD voltage (Human Body Model)	V _{ESD}	50	V
ESD voltage (Charged Device Model)	V _{ESD}	600	V

Outline Drawing

Unit: mm




Pin Configuration

PIN#	Description
1	Input
4	Output
2,3,5	Ground



Marking



Top View, Laser Marking

“H8”: Part Number

“.” Dot marking, indicates input

“1”: Terminal 1

The first “*”: Month Code (The code shown below varies in a 4-year-cycle)


Month	1	2	3	4	5	6	7	8	9	10	11	12
2016/2020	n	p	q	r	s	t	u	v	w	x	y	z
2017/2021	A	B	C	D	E	F	G	H	J	K	L	M
2018/2022	N	P	Q	R	S	T	U	V	W	X	Y	Z
2019/2023	a	b	c	d	e	f	g	h	i	j	k	m

The second “*”: Date Code


Date	1st	2nd	3rd	4th	5th	6th	7th	8th	9th	10th	
Code	A	B	C	D	E	F	G	H	J	K	
Date	11th	12th	13th	14th	15th	16th	17th	18th	19th	20th	
Code	L	M	N	P	Q	R	S	T	U	V	
Date	21st	22nd	23rd	24th	25th	26th	27th	28th	19th	30th	31st
Code	W	X	Y	Z	a	b	d	e	f	g	h

Typical Frequency Response


S21



Far side



Test Circuit



Stability Characteristics


ITEM	Test Item	STD Reference	Test Conditions	per lot
	Preconditioning	JESD22-A113	1) Temperature Cycling, 5 cycles -40°C to 85°C; 2) Bake, 24 hrs @85±5°C; 3)Moisture Soak, Soak time and conditions per IPC/JEDEC J-STD-020 based on device MSL level; 4) Reflow, 3 reflow cycles; 5) Drying, Room ambient temperature.	All behind
1	Temperature Cycling	JESD22-A104	-40°C / +85°C ,5°C/min, 15min dwell, < 1 min transfer time,500cycles	3*25 pcs
2	High Temperature Storage	JESD22-A103	Temperature = 85°C, 1000 hours.	3*25 pcs
3	Temperature Humidity no bias	JEDEC Std A101-B	85°C 85%RH 240 hours	3*25 pcs
4	Human Body Mode ESD	JESD22-A114	Ta=25°C, >100V	3 pcs
5	Charge Device Mode ESD	JESD22-C101	Ta=25°C, >100V	3 pcs
6	Solderability	JESD22-B102	Wetting: 245°C, 5s.	22 pcs
7	Drop Test	JESD22-B111	1500 Gs, 0.5 millisecond duration, half-sine pulse.	3*20 pcs
8	Mechanical Shock	JESD-47	Shock pulse of 1500g with pulse duration of 0.5+/-0. 1msec (X ,Y & Z); 5 shocks per axis.	3*25 pcs

Remarks


- SAW devices should not be used in any type of fluid such as water, oil, organic solvent, etc.
- Be certain not to apply voltage exceeding the rated voltage of components.
- Do not operate outside the recommended operating temperature range of components.
- Sudden change of temperature shall be avoided, deterioration of the characteristics can occur.
- Be careful of soldering temperature and duration of components when soldering.
- Do not place soldering iron on the body of components.
- Be careful not to subject the terminals or leads of components to excessive force.
- SAW devices are electrostatic sensitive. Please avoid static voltage during operation and storage.
- Ultrasonic cleaning shall be avoided. Ultrasonic vibration may cause destruction of components.

Packing Information

Carrier Tape




Reel Dimensions



Outer Packing

Type	Quantity	Dimension	Description	Weight
Carton Box I	50000	370×330×70mm	anti-static plastic bag & carton box 1 reel / bag	2.00kg
Carton Box II	100000	370×330×140mm	5 bags / box (50000pcs)	3.75kg
Carton Box III	200000	370×330×280mm	10 bags / box (100000pcs)	7.00kg
			20 bags / box (200000pcs)	

Recommended Soldering Profile



Remarks:

1. The specifications of this device are subject to change or obsolescence without notice.
2. Typically, equipment utilizing this device requires emissions testing and government approval, which is the responsibility of the equipment manufacturer.
3. Our liability is only assumed for the Surface Acoustic Wave (SAW) component(s) per se, not for applications, processes and circuits implemented within components or assemblies.
4. For questions on technology, prices and delivery, please contact our sales offices or e-mail sales@sainty-tech.com.